

INNOVATIVE 2 BOTTLE REFRIGERATED PROFESSIONAL SYSTEM WITH ENOMATIC® TECHNOLOGY

ELEGANT DESIGN, COMPACTNESS AND EASY INSTALLATION (PLUG & PLAY)

PERFECT ALSO FOR HOME USE

OPTION OF CONNECTING MULTIPLE SYSTEMS IN A LINE (MODULARITY)



eno one

- Available model: eno one 2/r (2 bottles in a line)
- Wine storage temperature: 6°C - 18°C (43°F-64°F)
- Installation: "plug & play"
- Gas supply:
Nitrogen E941 or Argon E938
(disposable or external cylinder; not included)
- Volumes: 1 free, 1 or 3 programmable
- Materials: stainless steel and black Gepax®
- Lighting system: LED lighting with adjustable intensity
- Bottle positioning system: self-centering lifted by pistons with gas spring
- Refrigeration system: with thermo-electric module
- Dispenser settings: via central touch-display
- Maintenance: light signal for tap cleaning
- Optional accessories:
 - Extra side panel (white or black color)
 - Connection kit
 - Spacer for short bottles
 - Gas canister cover
 - Dividing panel to separate bottles, 1 for white wines and 1 for red wines
 - Cylinder and pressure regulator: disposable argon canister (E938) 0,950lt - 32,12fl oz (sufficient for approx. 80 bottles)

Note: The image shows the model with extra side panels (white)



**INNOVATIVE
VENTILATION
SYSTEM**



**2 AREAS
1 FOR WHITE WINES
AND
1 FOR RED WINES**



model	W	H	D	Weight	Electrical system requirements
eno one 2/r	27,6 cm 10,88 inch	59,7 cm 23,49 inch	35,1 cm 18,83 inch	12 kg	100-240 V 50-60 Hz 70 W (based on market destination)