



enoline 2+2 R



enoline 4+4 R

**NEW GENERATION WINE SERVING SYSTEM
NEW COOLING SYSTEM, LOW NOISE LEVEL, HIGH PERFORMANCE
INNOVATIVE BOTTLE INSULATION SYSTEM TO PRESERVE WINE FLAVORS AND AROMAS**

enoline elite 2.5

- Available models:
 - enoline 2+2 bott. Refrigerated (4 bottles in a line)
 - enoline 4+4 bott. Refrigerated (8 bottles in a line) it is also possible to move the internal divider to offer a 5+3 configuration.
- Temperature: the system has a dual temperature compartment managed separately from 6 to 18 °C (from 43 to 64 °F) in order to serve both red and white wines.
- Cooling system: by refrigerator compressor.
- Use and system activation: the system can be used either behind the counter (without wine card) or self-service (with wine card).
- Gas supply: food grade Nitrogen or Argon (cylinder or generator not included).
- Volumes: 1 or 3 configurable volumes with touch screen key display.
- Display: each position has an LCD graphic touch screen interactive display to monitor the dispenser's functions. A central LCD graphic screen supplies general information.
- Materials: stainless steel, prepainted steel, glass.
- Colors and finishings: In addition to the classic stainless steel finish, it is possible to choose from the following colors: "black elegance, "black elegance precious" (pistons, handles and spouts in gold finish) or RAL customised colours (www.ralcolor.com).
- Lighting: double LED. Light intensity can be set; it changes according to different functions.
- Environment control: a junction box performs a check on all external environment conditions (temperature, pressure, humidity) in order to auto-adjust the dispenser's efficiency. This guarantees increased precision of pouring and better functionality of the refrigeration system.
- Nitrogen/Argon leak control: a designated pressure control system highlights any gas leak directly on the display.
- Bottle lifting system: by pneumatic pistons.
- Positioning: can be lined up on both sides; support furniture needed.
- Wine card types: chip card (SMART card) and RFID MIFARE (shared-use MAD system compatible). Finger print, magnetic stripe or bar code customizable upon request.
- Modules interfacing: LAN network, TCP/IP protocol.

models	W	H	D	Weight	Electrical requirements
enoline 2.5 2+2 R	20,91 in	26,38 in	13,87 in	95 lbs	100-240 V 50-60 Hz 115 W (based on market destination)
enoline 2.5 4+4 R	38,23 in	26,38 in	13,87 in	159 lbs	100-240 V 50-60 Hz 135 W (based on market destination)